

Profi - Check

Watch testing and measuring appliances

Elma Order Nos

Profi-Check	671 400 0000
-------------	--------------

incl. power supply



Pictured Profi - Check

External non-contact drive for setting crystal analoguous watches back in operation

The machine generates a magnetic rotating field with variable intensity and rotational speed around the watch support. As soon as an analoguous crystal watch is put in the range of influence of this rotating field, the magnetized rotor of the pulse motor also starts rotating. This allows very fast movement of the going parts without opening the watch, thereby removing gummy oil and dirt from the watch work.

Further product features

- functional checking of the mechanical parts
- loosening of locked-up going parts by fast movement
- correct setting of the watch hands
- checking of true running of going parts
- time setting
- indication of motor impulses
- checking of watch battery
- Magnetic surge generator:
 - Rotational speed: steplessly adjustable
 - Magnetising force: steplessly adjustable

Technical Data

Magnetic surge generator	Rotational speed: 5 – 200 impulses / sec.
Outer dimensions of unit w/d/h (mm / inch)	130 / 130 / 65 / 5 3/10 x 3 1/10 x 2 2/5
Weight (kg / lbs)	1.2 / 2.6
Power supply (incl. in delivery)	9 VDC



www.ert.pt
info@ert.pt
 Telf. 217 142 066 - Fax. 217 145 674

Rua Soeiro Pereira Gomes, Lote 5, Cave Drt.
 2845-387 Amora
 Portugal