

# Mini Centrifuge Z 130 M



Unlike traditional mini centrifuges, the new Z130M eliminates the need to change rotors when switching between microtubes and PCR strips. The included, unique COMBI-Rotor is all that is required for running 12 microtubes and 4 PCR strips simultaneously.

With a fixed speed that produces 5500rpm, this centrifuge is perfect for quick spin downs.




## Specifications

- Unique COMBI-Rotor for tubes and strips
- Twice the capacity of traditional mini centrifuges
- Starts & stops with closing/opening of the lid
- Compact, low profile design
- Short acceleration and deceleration times
- Low noise level 52 dBA
- Manufactured according to international safety regulations, e. g. IEC 61010



Unique COMBI-Rotor



Compact, low profile design

## Technical Data Z 130 M

max. Speed: 5500 rpm  
max. RCF: 2000 xg  
max. Volume: 12 x 1,5/2,0 ml tubes  
32 x 0,2 ml PCR tubes  
4 x PCR strips (8x0,2 ml)

Dimensions (W x H x D): 14 cm x 11,2 cm x 20 cm  
Weight: 1,3 kg

Order numbers:  
324.00 V01 - Z 130 M, 230 V / 50-60 Hz / 40 W  
324.00 V02 - Z 130 M, 120 V / 50-60 Hz / 40 W

# More from HERMLE:



**Refrigerated Microlitrecentrifuge Z 216 MK**

max. Speed: 15000 rpm  
max. Volume: 44 x 1,5/2,0 ml  
Example rotor: Angle rotor 24 x 1,5/2,0 ml



**Universal Centrifuge Z 306**

max. Speed: 13500 rpm  
max. Volume: 4 x 100 ml  
Example rotor: Swing out rotor 4 Places



**Refrigerated Universal Centrifuge Z 326 K**

max. Speed: 18000 rpm  
max. Volume: 4 x 100 ml  
Example rotor: Swing out rotor 4 Places



**Universal Centrifuge Z 326**

max. Speed: 18000 rpm  
max. Volume: 4 x 100 ml  
Example rotor: Swing out rotor 2 x 3 Microtitreplates



**Refrigerated High-Speed Centrifuge Z 36 HK**

max. Speed: 30000 rpm  
max. Volume: 6 x 250 ml  
Example rotor: Angle rotor 6 x 250 ml



**Universal Centrifuge Z 366**

max. Speed: 20000 rpm  
max. Volume: 6 x 250 ml  
Example rotor: Angle rotor 12 x 1,5/2,0 ml

**HERMLE Labortechnik GmbH**

Siemensstraße 25 • 78564 Wehingen • Germany

Phone: +49 (0) 74 26/96 22-50 • Telefax: +49 (0) 74 26/96 22-49

E-Mail: [vertrieb@hermle-labortechnik.de](mailto:vertrieb@hermle-labortechnik.de) • Web: [www.hermle-labortechnik.de](http://www.hermle-labortechnik.de)

