



350

350 Enterprise pH Meter

- Simultaneous pH and temperature display
- Storage of up to 32 results
- Automatic or manual calibration 500 hours battery life
- Application specific electrodes and consumables

The 350 is a general purpose portable pH meter offering 1 or 2 point pH calibration and automatic buffer recognition with manual override. It simultaneously displays both the temperature compensated pH readings and the manually set temperature.

Technical Specification

pH

Range	-2.00 to 16.00
Resolution	0.01
Accuracy	±0.02
Manual temperature range	0 to 100°C
Automatic buffer recognition	4.00, 7.00, 9.22, 10.00 (with manual override)
Calibration	User selectable 1 or 2 point
Connector	BNC
Power	2 AA batteries
Battery life	500 hours typical
Size (l x w x d)	175 x 75 x 35mm
Weight	250g

Ordering Information

Part Code	Description
350 201	350 pH meter supplied with epoxy bodied combination electrode (924 001), pH buffer sachets and batteries (fitted)
350 271	350 pH meter supplied with epoxy bodied combination electrode (924 001), pH buffer sachets, batteries (fitted) and free carry case

370 Enterprise Portable pH/mV Meter

- pH, absolute and relative mV ranges
- Automatic or manual calibration
- Automatic or manual temperature compensation
- Simultaneous pH and temperature reading
- Storage of up to 32 results

The 370 hand held pH/mV meter offers simple, yet professional performance with 1 or 2 point calibration and automatic buffer recognition with manual override. The unit simultaneously displays temperature compensated pH readings or electrode potential and temperature.

A comprehensive range of application specific electrodes and consumables are available for use with the 370 meter.

Technical Specification

pH	
Range	-2.00 to 16.00
Resolution	0.01
Accuracy	±0.02
Automatic buffer recognition	4.00, 7.00, 9.22, 10.00 (with manual override)
Calibration	User selectable 1 or 2 point
mV (absolute or relative)	
Range	±1999mV
Resolution	1mV
Accuracy	±1mV
Temperature	
Range	-10 to +105°C
Resolution	0.1°C
Accuracy	±0.5°C
ATC /Manual range	0 to 100°C
Connector	BNC
Power	2 AA batteries
Battery life	500 hours typical
Size (l x w x d)	175 x 75 x 35mm
Weight	250g

Ordering Information

Part Code	Description
370 201	370 pH/mV meter supplied with epoxy bodied combination electrode (924 001), ATC probe (027 500), pH buffer sachets and batteries (fitted)
370 271	370 pH/mV meter supplied with epoxy bodied combination electrode (924 001), ATC probe (027 500), pH buffer sachets, batteries (fitted) and free carry case



370