

PA 6.0 for O₂, CO₂ or O₂/CO₂



inclined display

Compact analyser for the monitoring of protective atmospheres in food packaging (MAP) and welding. For continuous analysis (in-line) and also intermittent sampling via a needle e.g. from food packs. A flexible analyser to guarantee quality and productivity of production processes.

Whenever you need a record of your measurement this instrument together with the exclusive WITT-LOGGER-Software is the solution.

Provide your customer with the results proving that your product has the best possible quality.

Benefits

- new operation by touch panel
- large illuminated graphic display
- Interfaces on front: mini SD and mini USB port
 - update possibility
 - data transfer via mini USB
- minimum sample gas required for analysing of smallest volumes (e.g. food packing)
- fast measuring results of sampling
- integrated data logger for the last 500 measurements
- assignment of measurements to different product names users and product lines
- multilingual menu guide: German, English, French, Italian, Spanish, Dutch, Swedish, Finnish, Polish, Hungarian, Romanian and Turkish (more to come)

- system errors or exceeding of set limits trigger an alarm and switch a potential free contact (e.g. to shut down machinery to avoid quality problems)
- splash-proof and robust housing
- interface for transfer of logged data

Options

- vertical or inclined display
- software WITT-LOGGER for recording of results incl. data cable (see separate data sheet)
- separate table printer for instant documentation
- Bluetooth (e.g. for separate printer)
- fully automatic calibration

Other models, options and accessories available on request.

Please identify the individual gases at the time of enquiring!

Measuring systems

Gases	Measuring system	Measuring range	Repeatability	Response time	Service life
O ₂ for sampling	chemical measuring cell	0-100%	± 0.2%	6 sec.	approx. 2 y. in air
O ₂ for continuous analysis	chemical measuring cell	0-100%	± 0.2%	10 sec.	approx. 3 y. in air
O ₂	zirconia measuring cell	0-25% *	± 0.1%	4 sec.	no limited
CO ₂	infrared measuring cell	0-30% 0-100% please indicate	± 0.5%	6 sec.	no limited

* no recommend for measures between 20 – 22%

Product Information

Technical Data

D01/C1 subject to change

GAS ANALYSERS
www.wittgas.com

Type	PA-O ₂ ; PA-CO ₂ ; PA-O ₂ /CO ₂
Finish	
P-version	over pressure measurement
L-version	measurement via lance with pump
S-version	sample measuring
Gases	O ₂ and/or CO ₂ ; balance gas: N ₂ , Ar (others on request) not for flammable, corrosive or toxic gases!
Measuring system	see table
Measuring range O₂/CO₂	0 – 100%; in 0.1%-steps
Sample gas requirement	O ₂ < 6 ml O ₂ /CO ₂ < 15 ml
Calibration O₂/CO₂	simple two point calibration
Withdrawal	
sample	automatic via needle using integrated pump
continuous	by pump or pressure regulator (optional)
Temperature (gas/environment)	5 – 40 °C (41 – 104 °F)
Gas connections	
sample	needle with integrated pump
continuous	hose connection for ID 4 mm with integrated pump
Inlet pressure	
pump	max. 0.3 barg
pressure regulator	max. 10 barg
L-version	pressureless
S-version	pressureless
Alarm contacts	2 potential free contacts for min. and max. settings (adjustable for each gas)
Interfaces	RS 232 with ASCII-output of date, time, measured value analog output 4-20 mA or 0-10 V
Housing	splash proof
Weight	approx. 3 kg
Dimensions (HxWxD)	approx. 145 x 105 x 250 mm (5.7 x 4.1 x 7.9 inch) (without connections)
Voltage	230 V AC, 110 V AC or 24 V DC
Power consumption	230 V AC, 0,07 A
Approvals	Company certified according to ISO 9001, ISO 14001 and ISO 22000 CE-marked according to: - EMC 2004/108/EC - Low Voltage Directive 2006/95/EC

